



CJX3-45 ~ 63  
(3TF46 ~ 47)



CJX3-75 ~ 85  
(3TF48 ~ 49)



CJX3-110 ~ 140  
(3TF50 ~ 51)

型号 Type		CJX3-32 3TB44	CJX3-32 3TB44	CJX3-38 3TF45	CJX3-38 3TF45	
额定绝缘电压(V) Rated insulation voltage		660	660	660	660	
额定工作电流(380V)(A) Rated operational current(380V)	AC-3	32	32	38	38	
	AC-4	15.6	15.6	18.5	18.5	
可控电机功率(kW) Rated outputs of three-phase motors at 50Hz	AC-3	230/220V	8.5	8.5	11	11
		400/380V	15	15	18.5	18.5
		500V	21	21	25	25
	AC-4	690/660V	23	23	23	23
		1000V	-	-	-	-
		400/380V	7.5	7.5	9	9
	690/660V	13	13	15.5	15.5	
机械寿命(*10 <sup>6</sup> ) Mechanical endurance		10	10	10	10	
电寿命(*10 <sup>6</sup> ) Electrical endurance	AC-3	1.2	1.2	1.2	1.2	
	AC-4	0.2	0.2	0.2	0.2	
操作频率(1/h) Switching frequency	AC-3	750	750	600	600	
	AC-4	250	250	200	200	
吸引线圈工作电压范围 Coil voltage tolerance		(0.8~1.1)Us				
吸引线圈功率消耗(AC) Power consumption of coil(50Hz)	保持(VA)/Closed	12.1	12.1	12.1	12.1	
	功率因数p.f.	0.28	0.28	0.28	0.28	
	吸合(VA)/Closed	101	101	101	101	
	功率因数p.f.	0.83	0.83	0.83	0.83	
约定发热电流(A) Convention althermal current		55	55	55	55	
辅助触头约定发热电流(A) Conventional thermal current of auxiliary contacts		10	10	10	10	
辅助触头额定工作电流(A) Rated operational current of auxiliary contacts	AC-15 380/220V	4/6	4/6	4/6	4/6	
重量(kg) Weight		AC0.68	AC0.8	AC0.68	AC0.8	

型号 Type		CJX3-45 3TF46	CJX3-63 3TF47	CJX3-75 3TF48	CJX3-85 3TF49	
额定绝缘电压(V) Rated insulation voltage		1000	1000	1000	1000	
额定工作电流(380V)(A) Rated operational current(380V)	AC-3	45	63	75	85	
	AC-4	24	28	34	42	
可控电机功率(kW) Rated outputs of three-phase motors at 50Hz	AC-3	230/220V	15	18.5	22	26
		400/380V	22	30	37	45
		500V	30	41	50	59
	AC-4	690/660V	39	55	67	67
		1000V	-	-	39	39
		400/380V	12.6/12	14.7/14	17.9/17	22/21
	690/660V	21.8/20.8	25.4/24.3	30.9/29.5	38/36	
机械寿命(*10 <sup>6</sup> ) Mechanical endurance		10	10	10	10	
电寿命(*10 <sup>6</sup> ) Electrical endurance	AC-3	1.2	1.2	1.2	1.2	
	AC-4	0.2	0.2	0.2	0.2	
操作频率(1/h) Switching frequency	AC-3	1200	1000	1000	850	
	AC-4	400	300	300	250	
吸引线圈工作电压范围 Coil voltage tolerance		(0.8~1.1)Us				
吸引线圈功率消耗(AC) Power consumption of coil(50Hz)	保持(VA)/Closed	17	17	32	32	
	功率因数p.f.	0.29	0.29	0.29	0.29	
	吸合(VA)/Closed	183	183	330	330	
	功率因数p.f.	0.6	0.6	0.6	0.6	
约定发热电流(A) Convention althermal current		80	90	100	100	
辅助触头约定发热电流(A) Conventional thermal current of auxiliary contacts		10	10	10	10	
辅助触头额定工作电流(A) Rated operational current of auxiliary contacts	AC-15 380/220V	4/6	4/6	4/6	4/6	
重量(kg) Weight		AC1.4/1.6	AC1.4/1.6	AC2.3/2.5	AC2.3/2.5	



CJX3-170 ~ 205  
(3TF52 ~ 53)



CJX3-250 ~ 300  
(3TF54 ~ 55)



CJX3-400 ~ 475  
(3TF56 ~ 57)

型号 Type		CJX3-110 3TF50	CJX3-140 3TF51	CJX3-170 3TF52	CJX3-205 3TF53
额定绝缘电压(V) Rated insulation voltage		1000	1000	1000	1000
额定工作电流(380V)(A) Rated operational current(380V)	AC-3	110	140	170	205
	AC-4	54	68	75	96
可控电机功率(kW) Rated outputs of three-phase motors at 50Hz	230/220V	37	43	55	64
	400/380V	55	75	90	110
	AC-3 500V	76	98	118	145
	690/660V	100	100	156	156
	1000V	65	65	90	90
	AC-4 400/380V 690/660V	28.4/27 49/56.9	36/35 63/60	40/38 69/66	52/50 90-86
机械寿命(*10 <sup>6</sup> ) Mechanical endurance		10	10	10	10
电寿命(*10 <sup>6</sup> ) Electrical endurance	AC-3	1.2	1.2	1.2	1.2
	AC-4	0.2	0.2	0.2	0.2
操作频率(1/h) Switching frequency	AC-3	1000	750	700	500
	AC-4	300	200	200	130
吸引线圈工作电压范围 Coil voltage tolerance		(0.8~1.1)Us			
吸引线圈功率消耗(AC) Power consumption of coil(50Hz)	保持(VA)/Closed	39	39	58	58
	功率因数p.f.	0.24	0.24	0.26	0.26
	吸合(VA)/Closed	550	550	910	910
	功率因数p.f.	0.45	0.45	0.38	0.38
约定发热电流(A) Convention althermal current		160	160	210	210
辅助触头约定发热电流(A) Conventional thermal current of auxiliary contacts		10	10	10	10
辅助触头额定工作电流(A) Rated operational current of auxiliary contacts	AC-15 380/220V	4/6	4/6	4/6	4/6
重量(kg) Weight		AC3.3/3.5	AC3.3/3.5	AC3.3/3.5	AC3.3/3.5

型号 Type		CJX3-250 3TF54	CJX3-300 3TF55	CJX3-400 3TF56
额定绝缘电压(V) Rated insulation voltage		1000	1000	1000
额定工作电流(380V)(A) Rated operational current(380V)	AC-3	250	300	400
	AC-4	110	125	150
可控电机功率(kW) Rated outputs of three-phase motors at 50Hz	230/220V	78	93	125
	400/380V	132	160	200
	AC-3 500V	178	210	184
	690/660V	235	235	375
	1000V	132	132	250
	AC-4 400/380V 690/660V	61/58 105/100	69/66 119-114	85/81 147/140
机械寿命(*10 <sup>6</sup> ) Mechanical endurance		10	10	10
电寿命(*10 <sup>6</sup> ) Electrical endurance	AC-3	1.2	1.2	1.2
	AC-4	0.2	0.2	0.2
操作频率(1/h) Switching frequency	AC-3	700	500	500
	AC-4	200	130	150
吸引线圈工作电压范围 Coil voltage tolerance		(0.8~1.1)Us		
吸引线圈功率消耗(AC) Power consumption of coil(50Hz)	保持(VA)/Closed	84	84	115
	功率因数p.f.	0.24	0.24	0.33
	吸合(VA)/Closed	1430	1430	2450
	功率因数p.f.	0.34	0.34	0.21
约定发热电流(A) Convention althermal current		300	300	400
辅助触头约定发热电流(A) Conventional thermal current of auxiliary contacts		10	10	10
辅助触头额定工作电流(A) Rated operational current of auxiliary contacts	AC-15 380/220V	4/6	4/6	4/6
重量(kg) Weight		AC6.2/6.4	AC6.2/6.4	AC8.5/8.7